

HAND PACKING

ERGONOMIC SOLUTION TO HAND PACKING



ERGOPACK®
Semi-Automatic Ergonomic Hand Pack Station

ERGOPACK MODELS

SPECIFICATIONS	ERGOPACK® 10	ERGOPACK® 12	ERGOPACK® 15	ERGOPACK® 20	ERGOPACK® 25	ERGOPACK® 30	ERGOPACK® XL 10	ERGOPACK® XL 15
Max. Speed	10 CPM	12 CPM	15 CPM	20 CPM	25 CPM	30 CPM	10 CPM	15 CPM
Max. Case Range	24"x 16" x24"	20"x 13.5"x19"	24" x 16" x18"	24" x 16" x18"	24" x 16" x18"	20" x 13.5" x18"	24" x 20" x18"	24" x 20" x18"
Min. Case Range	13"x 7.75"x 6"	8.5"x 4.75"x 4"	8"x 6"x 5"	8"x 6"x 5"	8"x 6"x 5"	8"x 6"x 5"	8"x 6"x 5"	8"x 6"x 5"
Magazine Capacity	50" ~150 Cases	50" ~150 Cases	50" ~150 Cases	50" ~150 Cases	50" ~150 Cases	50" ~150 Cases	50" ~150 Cases	50" ~150 Cases
Case Modification Available	Y	Y	N	Y	Y	Y	N	Y
Glue Option	Y	Y	Y	Y	Y	Y	N	Y
Washdown Option	IP54 / IP69K	IP54 / IP69K	IP54 / IP69K	IP54 / IP69K	IP54 / IP69K	IP54 / IP69K	IP54 / IP69K	IP54 / IP69K
Std. Voltage	240V/3PH	240V/3PH	240V/3PH	240V/3PH	240V/3PH	240V/3PH	240V/3PH	240V/3PH
SCFM- 80 PSI -3/4 Supply Line	18 SCFM	14-18 SCFM	18-20 SCFM	18-20 SCFM	8-10 SCFM	8-10 SCFM	16-18 SCFM	16-18 SCFM
Footprint (2-Person)	9'8" x 19'11"	8'11" x 17'8"	9'7" x 20'4"	9'7" x 21'6"	9'7" x 21'6"	9'7" x 21'6"	10'4" x 22'3"	10'4" x 22'3"
Approx. Shipping Weight	~2400 lbs.	~2400 lbs.	~2400 lbs.	~2400 lbs.	~2400 lbs.	~2400 lbs.	~2400 lbs.	~2400 lbs.
Std. Finish	Steel Plus 316 is a two component, water base epoxy filled with 316 stainless steel flake. Finish Color is a Steel-It Grey and is USDA and FDA accepted.							
Controls	AB COMPACT LOGIX PLC with PV+ Color TS							
Available Options	1-2-3-4 Operator Stations, Low Case, Low Tape, Extended Magazine, Casters, Stack Lights, Elevation Kits, Spare Parts							